

MADRA-EDM

Bohrerrodieranlagen

Low cost
starter model

Original




Madra-Bohrteufel

high-class - long-lasting - reasonably priced

MADRA BT-1.500

- o demanding applications require highly productive machines
- o drillings with electrode diameters from 0.3 to 3 mm into:



- o hardened steel
- o carbide
- o stainless steel
- o copper
- o brass
- o aluminium



Information

MADRA-EDM GmbH
Lange Hecke 4
63796 Kahl / Main
Germany
phone: +49 6188 9141 920
fax: +49 6188 9141 922
info@madra-edm.de
www.madra-edm.de

The best recommendation for our "BOHRTEUFEL"
are the people operating it.

Technical data on back side
Subject to change

MADRA BT-1.500

technical details

clamping area	mm	600 x 400
max. work piece height	mm	300
X-stroke	mm	500
Y-stroke	mm	400
adjustable range W-axis	mm	250
servo-controlled Z-axis	mm	0,01 - 380
max. electrode length	mm	400
max. work piece weight	kg	500
area	mm	1300 x 1300
total height	mm	1980
total weight	kg	980

- motor adjustable W-axis (rough adjustment)
- electrode diameters from 0.3 - 3.0 mm
- electrodes up to 400 mm length
- stone table
- electrode collet via gear rim chuck
- halogen machine lamp
- drilling depth free programmable automatic depth swith-off
- drill pattern programmable

